AT SERIES



Rated load from 60 kg to 125 kg. This air hoist series uses a surface-hardened load chain made of high-strength alloy steel with excellent wear resistance. Buttons on the pendant make operation easy. The load chain can be extended. Models AT-60-K-5 and AT-125-K-5 come with an emergency stop button on the pendant as standard.

Endo Air Hoist Specifications – AT Series

Model	Rated load (kg)	Stroke (m)	Air pressure (MPa)	Lifting speed (m/min)	Air consumption (m³/min)	Load chain (size × falls)	Air inlet	Weight (kg)	Emergency stop
AT-60K	60	3	0.4	16.5	0.52	4.0×1	Rc 3/8	12.3	–
			0.5	20.0	0.67				
			0.6	23.5	0.85				
AT-60K-5	60	3	0.4	16.5	0.52	4.0×1	Rc 3/8	13.0	•
			0.5	20.0	0.67				
			0.6	23.5	0.85				
AT-125K	125	3	0.4	10.0	0.55	4.0×1	Rc 3/8	12.5	–
			0.5	12.0	0.71				
			0.6	14.5	0.90				
AT-125K-5	125	3	0.4	10.0	0.55	4.0×1	Rc 3/8	13.2	•
			0.5	12.0	0.71				
			0.6	14.5	0.90				

Models marked "-5"

come with an emergency stop button as standard. Lifting speed and air consumption vary with supply pressure.

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198

Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806

Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.