EHL-TS SERIES



Rated load from 250 kg to 3000 kg. This air hoist series uses a surface-hardened load chain made of alloy steel with outstanding strength and wear resistance. The load chain can be extended as required. A pull cord is the standard control for lifting and lowering. For push-button control, a separate pendant switch must be purchased. Note: The EHL-3TS model is sold only outside Japan and cannot be used in Japan.

EHL-TS Air Chain Hoist

Model	Rated load (kg)	Lifting height (m)	Air pressure (MPa)	Lifting speed (m/min)	Air consumption (m^3/min)	Chain (mm × falls)	Air inlet	Weight (kg)
EHL-025TS	250	3	0.4 (4)	12.0	0.9	6.3×1	Rp 1/2	20.0
			0.5 (5)	16.0	1.3			
			0.6 (6)	18.0	1.6			
EHL-05TS	500	3	0.4 (4)	7.5	0.95	6.3×1	Rp 1/2	20.0
			0.5 (5)	9.0	1.3			
			0.6 (6)	10.5	1.65			
EHL-1TS	1000	3	0.4 (4)	4.0	1.0	7.1×1	Rp 1/2	34.0
			0.5 (5)	5.2	1.4			
			0.6 (6)	6.0	1.8			
EHL-3TS	3000	3	0.4 (4)	2.0	1.75	12.5×1	Rp 3/4	79.0
			0.5 (5)	2.6	2.47			
			0.6 (6)	3.0	3.14			

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198
Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806
Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.