EHV SERIES (CE MARKED MODEL)



This air hoist series has a rated load of 250 kg to 1000 kg . It is equipped with a surface-hardened load chain made of alloy steel with high impact strength and outstanding wear resistance .

EHV Air Hoist

Working air pressure 0.4 – 0.6 MPa · Standard lifting height 3 m · Air inlet Rp 1/2

Model	Control	Rated load (kg)	Lifting height (m)	Air pressure (MPa)	Lifting speed (m/min)	Air consumption (m³/min)	Chain (mm × falls)	Air inlet	Weight (kg)
EHV25SP	Push-button	250	3	0.4 – 0.6	12 – 18	0.9 – 1.6	6.3×1	Rp 1/2	23.0
EHV50SP	Push-button	500	3	0.4 – 0.6	7.5 – 10.5	0.95 – 1.65	6.3×1	Rp 1/2	23.0
EHV98WP	Push-button	980	3	0.4 – 0.6	3.7 – 5.2	0.95 – 1.65	6.3×2	Rp 1/2	29.0
EHV100WP-OP	Push-button	1000	3	0.4 – 0.6	3.7 – 5.2	0.95 – 1.65	6.3×2	Rp 1/2	31.0
EHV25SC	Pull cord	250	3	0.4 – 0.6	12 – 18	0.9 – 1.6	6.3×1	Rp 1/2	21.0
EHV50SC	Pull cord	500	3	0.4 – 0.6	7.5 – 10.5	0.95 – 1.65	6.3×1	Rp 1/2	21.0
EHV98WC	Pull cord	980	3	0.4 – 0.6	3.7 – 5.2	0.95 – 1.65	6.3×2	Rp 1/2	27.0
EHV100WC-OP	Pull cord	1000	3	0.4 – 0.6	3.7 – 5.2	0.95 – 1.65	6.3×2	Rp 1/2	29.0

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198

Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806

Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.