EHW-R



This air hoist series is designed for simple, easy operation via a pendant switch. It is also equipped with a reverse-winding prevention device , and the air motor stops automatically when the wire rope is paid out to 1.9 m .

Technical Specifications

The Endo EHW-R air hoist series is operated by a pendant switch for easy, safe control. It features a reverse-winding prevention mechanism and stops automatically when the wire rope reaches the end of its 1.9 m stroke.

Model	Rated load (kg)	Stroke (m)	Air pressure (MPa)	Lifting speed (m/min)	Air consumption (m^3/min)	Air inlet	Weight (kg)
EHW-60R	60	1.9	0.4	18.5	0.55	Rc 3/8	9.5
			0.5	22.5	0.70		
			0.6	26.0	0.88		
EHW-120R	120	1.9	0.4	11.0	0.59	Rc 3/8	9.7
			0.5	13.5	0.75		
			0.6	16.0	0.93		

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198
Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806
Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.