EHW SERIES



Working load from 60 kg to 120 kg. The up/down controls and handle are mounted directly on the bottom hook. While keeping the suspended load stable, this air hoist offers better control than a separate pendant-cord type. It is equipped with a reverse-winding prevention mechanism, and the air motor stops automatically when the wire rope is paid out to its full 1.9 m stroke.

Technical Specifications

Model	Rated load (kg)	Stroke (m)	Air pressure (MPa)	Lifting speed (m/min)	Air consumption (m^3/min)	Air inlet	Weight (kg)
EHW-60	60	1.9	0.4 (4)	18.5	0.55	Rc 3/8	9
			0.5 (5)	22.5	0.70		
			0.6 (6)	26.0	0.88		
EHW-120	120	1.9	0.4 (4)	11.0	0.59	Rc 3/8	9
			0.5 (5)	13.5	0.75		
			0.6 (6)	16.0	0.93		

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198
Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806
Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.