FS-Ann160S-VBR



This cleanroom electric lifter series is designed for light lifting tasks: 80kg load capacity, 24V/10AH battery, 125mm/s lifting speed and a maximum lifting height of 1900mm. Fast 4-hour charging, IP41 rated with an optional IP66 upgrade. Swivel or fixed front wheels are available, making it suitable for flexible production environments and confined spaces.

Specifications - Models S1160 / S1190 / S1220

Parameter	S1160	S1190	S1220
Mast height *Mast height (mm)*	1600	1900	2200
Lifting height *Lifting height (mm)*	1300	1600	1900
Lifting speed *Lifting speed (mm/s)*	125 mm/s	125 mm/s	125 mm/s
Protection class *IP protection*	IP41	IP41	IP41
Battery *Battery*	24V / 10AH lead-acid	24V / 10AH lead-acid	24V / 10AH lead-acid
Charger input *Charging power supply*	100–240VAC, 50/60Hz	100–240VAC, 50/60Hz	100–240VAC, 50/60Hz
Charging time *Charging time*	4 hours	4 hours	4 hours
Load capacity *Load capacity*	80kg		

Upgrade Options

Option	Description
IP Protection	IP66
Ø75mm Swivel wheel	Front leg height 92mm
Ø80mm Fixed wheel	Front leg height 85mm

Note: can be customized to your actual application requirements.

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198
Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806
Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.