FS-Ann230A-RCS



The FS-Ann230A-RCS compact electric lifter has a 304 stainless steel frame and is built for logistics and factory environments with strict hygiene requirements. Lifting height up to 2000mm, 80kg load capacity, and a mobile roller platform for easy handling. It runs on a DC24V battery with a lifting speed of 125 mm/s and fits standard baskets and plastic crates. Optional upgrades include position locking, flexible casters and a lithium battery for higher performance.

Specifications - 80kg Cleanroom Lifter Series

Parameter	S1160	S1190	S1220
Mast height *Mast height (mm)*	1600	1900	2200
Lifting height *Lifting height (mm)*	1300	1600	1900
Lifting speed *Lifting speed (mm/s)*	125 mm/s	125 mm/s	125 mm/s
Protection class *IP Protection*	IP41	IP41	IP41
Battery *Battery*	24V / 10AH lead-acid	24V / 10AH lead-acid	24V / 10AH lead-acid
Charger input *Charging power*	100–240VAC, 50/60Hz	100–240VAC, 50/60Hz	100–240VAC, 50/60Hz
Charging time *Charging time*	4 hours	4 hours	4 hours
Load capacity *Load capacity*	80kg		

Upgrade Options

Option	Description
IP Protection	IP66
Ø75mm Swivel wheel	Front leg height 92mm
Ø80mm Fixed wheel	Front leg height 85mm

Note: can be customized to suit the customer's actual application.

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198
Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806
Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.