

FS-D2B-F Two-Speed Servo Hoist 125kg-500kg



FS-D2B-F HOIST

PRODUCT FEATURES

- Automatic slowdown when approaching the upper limit reduces upper limit switch faults, and the lifting/lowering working range can be set flexibly;
- Ergonomically designed handle with a comfortable grip. The two-speed control lever lets the operator lift and lower materials easily with one hand, and operation can be switched freely between hands;
- More accurate positioning, with smoother operation, lift-off, and set-down, making full use of the smart hoist's speed, precision, and stability;
- High cost-performance, suitable for all types of hoist workstations. It reduces labor intensity, raises the level of smart equipment, and keeps automated lines running at a fast cycle time.

SPECIFICATIONS

MODEL ITEM	FS-D2B012-F	FS-D2B025-F	FS-D2B050-F
Rated load (kg)	125	250	500
Lifting speed - Two-speed (m/min)	1/12	1/12	1/8
Rated power (kW)	0.75	0.75	1.1
Maximum lift (m)	2.8 (Customizable)		

MODEL ITEM	FS-D2B012-F	FS-D2B025-F	FS-D2B050-F
Control mode	FS-F3 Two-Speed Servo Handle		
Unit weight (kg)	25	25	31
Chain size (mm)	5.0	5.0	5.0
Power supply	Standard 380V (220V optional)		
Mechanism duty class	3m/M6	3m/M6	3m/M6
Operating temperature (°C)	-10°C ~ 55°C		

Note: The above specifications are for model selection reference only; the nameplate supplied with the unit shall prevail.

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198

Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806

Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.