FS-Flash(lite)220A-CTR



Load capacity: 120KG (dimensions can be customized to customer requirements) Overall equipment height: 2.2m Overall stacking height approx. 2m (bins can be picked up and tilted easily on the left and right) Height memory: 3 working positions, each with 5 memory levels, for a total of 15 height memory levels Switchable between manual and automatic modes Automatic mode: one button to tilt, one button to return to the home position Body material: aerospace-grade aluminum alloy + stainless steel Safe and hygienic, a reliable assistant for industrial and food applications.

Specifications

Parameter	A4190	A4220
Mast height (mm) ***Mast height***	1900	2200
Lifting height (mm) ***Lifting height***	1500	1800
Lifting speed ***Lifting speed***	250mm/s	250mm/s
Protection rating ***IP Protection***	IP41	IP41
Battery ***Battery***	24V/10AH lead-acid battery	
Charging voltage ***Charging voltage***	100–240VAC, 50/60Hz	
Charging time ***Charging time***	4 hours	
Optional upgrades ***Optional upgrades***	Lithium battery 24V/15AH Charging voltage 115/230VAC Fast charging: 1 hour	
Front wheels ***Front wheel options***	ø75mm swivel ø80mm fixed	

Parameter	A4190	A4220
Load capacity ***Load capacity***	120kg	

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198

Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806

Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.