

FS-Q6L Intelligent Balancing Electric Hoist 100kg-600kg



Note: See Optional Control Handles for detailed handle configurations

FS-Q6L INTELLIGENT

PRODUCT FEATURES

Automatic Slowdown
at Upper Limit

Handle Mode · Float Mode · Precise Positioning · Overload Protection · Stepless Speed Control · Photoelectric Sensor · Anti-Rebound · Power-Loss Protection

SPECIFICATIONS

MODEL ITEM	FS-Q6L010-B6	FS-Q6L020-B6	FS-Q6L030-B6	FS-Q6L050-B6	FS-Q6L060-B6
Rated load (kg)	100	200	300	500	600
Lifting speed (m/min)	0~16	0~13	0~11	0~10	0~8
Rated power (kW)	0.55	0.75	1.1	1.5	1.5
Standard lift (m)	2.8 (Customizable)				

MODEL ITEM	FS-Q6L010-B6	FS-Q6L020-B6	FS-Q6L030-B6	FS-Q6L050-B6	FS-Q6L060-B6
Control mode	Coaxial Slide Handle				
Self weight (kg)	37	37	48	48	48
Chain size (mm)	5.0	5.0	6.3	6.3	6.3
Power supply	Standard 1-phase 220V (3-phase 380V)				
Mechanism duty class	3m/M6				
Operating temperature (°C)	-10°C ~ 55°C				

Note: The above specifications are for model selection reference only. Please refer to the nameplate supplied with the product for actual specifications.

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198

Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806

Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.