FS-Wilson-VAT



FS-Wilson190S-VAT – a reliable assistant for the food and pharmaceutical industries If you have special requirements or face difficulties in material handling, contact us and we will design the most suitable solution for you.

Specifications - Wilson VAT Series Lift and Tip Unit

Model	Wilson-VAT190	Wilson-VAT220	Wilson-VAT250	Wilson-VAT270
Spindle height H	1900	2200	2500	2700
Tipping lift height T	1300	1600	1900	2100
Working height C	2400	2700	3000	3200
Operation panel	☐ Battery indicator light ☐ Manual / automatic mode ☐ Manual mode – inching lift and rotation ☐ Automatic mode – one-button automatic lift, rotate, pour and return ☐ EMS emergency stop button ☐ Comes with wired remote control			
Pouring method	Manual feeding, manual fastening, electric lifting and dumping			
Load	80kg (excluding container)			
Applicable containers	☐ 60L ☐ 80L ☐ 100L 304 stainless steel mixing tank ☐ Spout type ☐ Full-round type **** Only one tank size per lifting arm**			
Lifting speed	125 mm/s			

Model	Wilson-VAT190	Wilson-VAT220	Wilson-VAT250	Wilson-VAT270
Protection level	IP66			
Battery	DC24V20AH			
Charging	Input 100~240V AC			
Material	304 stainless steel			

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198

Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806

Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.