FS-Wilson190S-ATS



The S2160/S2190/S2220 cleanroom electric lifters are compact, with a 200kg lifting capacity, suited to factories, warehouses and production lines. They use a 24V/20AH battery, lift at 125mm/s and reach lifting heights from 1200mm to 1800mm. Charging time is 6–8 hours, IP41 rated with an optional IP66 upgrade. Swivel or fixed front wheels are available to suit each floor condition. An effective solution for fast, safe lifting tasks.

Specifications - 200kg Cleanroom Lifter Series

Parameter	S2160	S2190	S2220
Mast height *Mast height (mm)*	1600	1900	2200
Lifting height *Lifting height (mm)*	1200	1500	1800
Lifting speed *Lifting speed (mm/s)*	125 mm/s	125 mm/s	125 mm/s
Protection class *IP Protection*	IP41	IP41	IP41
Battery *Battery*	24V / 20AH lead-acid	24V / 20AH lead-acid	24V / 20AH lead-acid
Charger input *Charging power*	100–240VAC, 50/60Hz	100–240VAC, 50/60Hz	100–240VAC, 50/60Hz
Charging time *Charging time*	6~8 hours	6~8 hours	6~8 hours
Load capacity *Load capacity*	200kg		

Upgrade Options

Option	Description
IP Protection	IP66
Ø75mm Swivel wheel	Front leg height 110mm
Ø80mm Fixed wheel	Front leg height 85mm

Note: can be customized flexibly to the customer's actual needs.

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198
Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806
Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.