FS-WilsonX190A-FAC



This cleanroom electric lifter is an efficient lifting solution for loads up to 200kg, with lifting heights from 1200mm to 1800mm. It is equipped with a 24V/20AH battery, 125mm/s lifting speed and a 6–8 hour charging time. The rigid frame is IP41 rated, with an optional IP66 upgrade and wheel options for different floor conditions. Suited to warehouses, factories, clean environments and tasks that require precise handling.

Specifications - Models S2160 / S2190 / S2220

Parameter	S2160	S2190	S2220
Mast height *Mast height (mm)*	1600	1900	2200
Lifting height *Lifting height (mm)*	1200	1500	1800
Lifting speed *Lifting speed (mm/s)*	125 mm/s	125 mm/s	125 mm/s
Protection class *IP protection*	IP41	IP41	IP41
Battery *Battery*	24V / 20AH lead-acid	24V / 20AH lead-acid	24V / 20AH lead-acid
Charger input *Charging power supply*	100–240VAC, 50/60Hz	100–240VAC, 50/60Hz	100–240VAC, 50/60Hz
Charging time *Charging time*	6–8 hours	6–8 hours	6–8 hours
Load capacity *Load capacity*	200kg		

Upgrade Options

Option	Description
IP Protection	IP66
Ø75mm Swivel wheel	Front leg height 110mm
Ø80mm Fixed wheel	Front leg height 85mm

Note: can be customized to your actual application requirements.

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198
Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806
Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.