FS-YFX



Vacuum Lifter Specifications

Model	Safe working load	Dimensions (mm)	Pad diameter	Number of pads	Voltage	Control	Function
FS–YFX1500–16S	1500KG	(1375+2500+1375)×1340×580	Φ300	16 pcs	DC24V	Wireless remote control	0–90° hydraulic tilt + 0–360° hydraulic rotation
FS–YFX2000–22S	2000KG	(1375+2500+1375)×1340×580	Φ300	22 pcs			
FS–YFX2500–26S	2500KG	(1375+2500+1375)×1340×580	Φ300	26 pcs			
FS–YFX3000–8S	3000KG	(1250+2500+1250)×1800	1000×640	8 pcs	DC24V	Wireless remote control	0–90° hydraulic tilt + 0–360° hydraulic rotation
FS–YFX5T–12S	5T	(2000+4300+2000)×1900	1000×640	12 pcs	DC24V	Wireless remote control	0–90° hydraulic tilt + 0–360° hydraulic rotation

Model	Safe working load	Dimensions (mm)	Pad diameter	Number of pads	Voltage	Control	Function
FS–YFX10T–20S	10T	(3000+6000+3000)×1900	1000×640	20 pcs	DC24V	Wireless remote control	0–90° hydraulic tilt + 0–360° hydraulic rotation

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198
Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806
Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.