FS-YFXA



Technical Specifications

Models	Safe working load	Dimensions (mm)	Pad size (mm)	Number of pads	Power system	Control	Function
FS–YFXA1000–2S	1000kg	3270×560	1150×560	2 pcs	DC24V	Wireless remote control	0–90° hydraulic tilt + 0–360° hydraulic rotation
FS–YFXA2000–4S	2000kg	2500×1800	1150×560	4 pcs	DC24V	Wireless remote control	
FS–YFXA3000–8S	3000kg	(1250+2500+1250)×1800	1150×560	8 pcs	DC24V	Wireless remote control	
FS–YFXA5000–12S	5000kg	(2000+4300+2000)×1900	1150×560	12 pcs	DC24V	Wireless remote control	
FS–YFXA10T–20S	10T	(3000+6000+3000)×1900	1150×560	20 pcs	DC24V	Wireless remote control	

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198
Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806
Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.