Hydraulic Cable Reel Clamp Lifter











Specifications

Model	FSCPD0516Z-500	FSCPD0525Z-500	FSCPD0516Z-1000	FSCPD0525Z-1000	FSCPD1025Z-1500
Load Capacity (kg)	500	500	500	500	1000
Max. Lift Height (mm)	1600	2500	1600	2500	2500
Roll Diameter (mm)	200-500	200-500	600-1000	600-1000	800-1500
Battery (V/Ah)	24/200	24/200	24/200	24/200	24/200
Charger (V/Ah)	24/30	24/30	24/30	24/30	24/30
Self-weight (kg)	1048	1250	1460	1640	1860
Overall Size (mm)	2500*950*2000	2500*950*1785	2900*1500*2000	2900*1500*1785	3300*1900*1785
Lift Motor (kw)	2.5	2.5	2.5	2.5	2.5

Model	FSCPD0516Z-500	FSCPD0525Z-500	FSCPD0516Z-1000	FSCPD0525Z-1000	FSCPD1025Z-1500
Drive Motor (kw)	AC1.5	AC1.5	AC1.5	AC1.5	AC1.5
Gradeability (%)	4/6	4/6	4/6	4/6	4/6
Working Aisle (mm)	2900	2900	3600	3600	4000
Travel Aisle (mm)	1000	1000	1600	1600	1900
Service Brake	Electromagnetic Braking				

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198
Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806
Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.