Mini Crane 400 kg (Manual Push)











400 kg Push-Type Mobile Crane

Dimension drawing:

Key Features

- Choice of **manual pushing** or powered travel for higher efficiency and safety
- **360°** rotating boom for easy lifting and handling at many different positions
- **8-function wireless push-button** control system for smooth operation, with emergency stop
- Sturdy, easy-to-maintain design suited to both workshops and modern factories
- **Applications:** Widely used in factories, logistics warehouses and industrial parks; especially convenient for lifting equipment, materials, components, machinery, motors...



400 kg push-type electric crane - View 1



400 kg push-type electric crane - View 2



400 kg push-type electric crane - View 3

FS-400-BZD Detailed Specifications

Parameter	Unit	Value
Model	-	FS-400-BZD
Electric winch control method	-	Electric control
Boom rotation	-	Manual
360° rotation	-	Yes
Max. load at shortest boom	kg	400
Max. load at longest boom	kg	300
Max. boom length (horizontal)	mm	1150-1450
Hydraulic cylinder stroke	mm	400
Distance from base leg to hook	mm	500-1150
Retracted dimensions (L×W×H)	mm	1760×940×1820
Base plate dimensions (L×W)	mm	1300×940
Max. overall height	mm	2820
Max. lifting height (hook)	mm	2330
Main wheel diameter	mm	200
Hydraulic pump power	kW	1.5
Electric motor (voltage/power)	V/W	/
Battery	V/A	12/120
Charger	V/A	12/12
Included wireless remote		8 buttons
Full battery charging time	h	8
Continuous operation per charge	h	~4.5
Travel method	-	Manual push or electric drive
Unit weight (excluding counterweight)	kg	330
Packing dimensions (L×W×H)	m	1.45×1.15×1.94

Parameter	Unit	Value
Packed weight	kg	450

Contact us for consultation and a quotation

Vietnam factory: Workshop A1-1, VSIP Hai Phong, Nam Trieu Ward, Hai Phong City · +84 817 888 198
Taiwan factory: Zhongli District, Taoyuan City · +886 3-451-8806
Email: sales@fullsharp.com.vn · **Website:** www.fullsharp.com

Specifications may vary with the ordered configuration. Please contact FullSharp for exact details.